



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>A61M 15/00</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/21601</b></p> <p>(43) International Publication Date: 6 May 1999 (06.05.99)</p>
<p>(21) International Application Number: PCT/GB98/03170</p> <p>(22) International Filing Date: 23 October 1998 (23.10.98)</p> <p>(30) Priority Data: 9722285.5 23 October 1997 (23.10.97) GB</p> <p>(71) Applicant (for all designated States except US): RHONE-POULENC RORER LIMITED [GB/GB]; RPR House, 50 Kings Hill Avenue, Kings Hill, West Malling, Kent ME19 4AH (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): CLARKE, Alastair, Robert [GB/GB]; Rhone-Poulenc Rorer Limited, London Road, Holmes Chapel, Cheshire CW4 8BE (GB).</p> <p>(74) Agent: CAFFIN, Lee; Rhone-Poulenc Rorer Limited, Patent Dept., London Road, Holmes Chapel, Cheshire CW4 8BE (GB).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: INHALATION DEVICE</p> <div data-bbox="316 1155 1266 1638"> </div> <p>(57) Abstract</p> <p>An inhalation device which contains powdered medicament in the form of a medicament compact is provided with a seal comprising a partial ring between the outer wall and inner mandrel of the medicament compact chamber. The medicament is dispensed by abrading the medicament compact by turning the compact relative to the inner mandrel against a blade. Despite only extending around part of the circumference of the mandrel the seal prevents leakage of loose powder from the compact chamber to the rest of the device. The sealing means also provides a frictional braking force on the medicament reservoir sufficient to prevent movement of the medicament reservoir when the drive mechanism for the reservoir is returning to its starting position without making the device difficult to operate by a child or infirm adult.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

### INHALATION DEVICE

This invention relates to a device for the administration of powdered medicaments by inhalation, more particularly to a multiple-dose inhalation device with metering means for  
5 dispensing pre-determined doses from a medicament reservoir.

European Patent 407028 discloses a multiple-dose inhalation device in which a dose of medicament is metered by abrading a fixed volume from a compacted body of powdered medicament. In a preferred embodiment of this device the compacted body of medicament  
10 comprises a cylinder which is held within a reservoir and which fits over an inner mandrel. The mandrel provides support for some or all of the medicament compact and provides an axis around which the reservoir and compact is turned in order to abrade a dose of medicament from the compact. The metered dose is then entrained in a through-going pathway of the device and is inhaled by the patient, the means for abrading being, for  
15 example, a helical blade.

The device of EP 407028 was improved in EP 691865 by providing a shuttering system to isolate the compacted body of medicament from the through-going pathway of the device. However, during transport powder still tended to leak from the medicament compact to the  
20 outer mechanism.

We have now found that this leakage can be greatly reduced by provision of a partial sealing means between the medicament reservoir and the inner mandrel of the inhalation

device. Surprisingly it has been found that although a gap must be left in the sealing means in order to accommodate the pathway between the medicament reservoir and the dispersion chamber leakage is substantially reduced. Another advantage of the seal is that it provides a frictional brake which allows the ratchet mechanism rotating the medicament reservoir to  
5 cause abrasion of the medicament compact therein to return to its starting position without concomitant movement of the medicament reservoir.

Thus, according to one aspect of the invention, there is provided a medicament inhalation device including a housing having a through-going pathway connecting an air inlet with an  
10 air outlet, a medicament reservoir adapted to receive a compacted body of powdered medicament, an inner mandrel around which the medicament reservoir rotates and metering means for dispensing a predetermined dose of medicament from the reservoir into the pathway, the metering means including means for abrading the compacted body; characterised in that there is provided between the medicament reservoir and the inner  
15 mandrel of the device a sealing means extending round less than  $360^\circ$  of the mandrel.

In a further aspect of the invention the sealing means is adapted to provide a frictional braking force on the medicament reservoir sufficient to prevent movement of the medicament reservoir when the ratchet mechanism designed to cause rotation of the  
20 reservoir is returning to its starting position but which force is not so large as to make the device difficult to operate by a child or infirm adult. Typically this force will comprise a torque of between 0.1 and 0.6 Newton metres (Nm), preferably between 0.2 and 0.5Nm and most preferably about 0.4Nm.

The sealing means may be produced as an integral feature of the inner mandrel in a single production operation. This may be particularly advantageous when the material of construction of the mandrel is such that the sealing means feature is suitably resilient to produce the required seal and/or frictional braking effects.

5

The sealing means may be added to the mandrel during production by any standard process method, allowing the mandrel body and sealing ring to be formed from different materials. One such method is known as insert moulding. In insert moulding the mandrel body is formed by a standard moulding process. The mandrel body is transferred to a separate tool  
10 where the sealing means is moulded into position on the mandrel body. This process gives a good mechanical fit between the mandrel body and the sealing means but no adhesive or chemical bond. A second method is co-moulding. The mandrel body is formed by a standard moulding process. Co-incident with or slightly after the formation of the mandrel the sealing means is moulded in place using the same machine. In this process a chemical  
15 or adhesive bond is formed between the sealing means and the mandrel body.

Alternatively the sealing means may comprise a separate partial sealing ring. It is preferred that the sealing ring be formed in a single moulding process rather than being provided as a complete ring and cut to size.

20

The sealing means may conveniently be produced from any suitable resilient material. It is important that the material be compatible with the medicament and excipients used to form

the medicament compact. ABS or Polyolefin plastic materials are preferred and a particularly preferred material is polypropylene.

The ring may be of any cross sectional shape capable of providing a good seal. A particularly advantageous shape for the cross section is a generally 'V' shape with the point of the 'V' aligned to face the medicament compact. Preferably the arm of the 'V' next to the inner mandrel is flush with the mandrel. The section of the ring in contact with the inner mandrel may be thicker and, therefore, less flexible than the section sealing the medicament reservoir. Where the sealing means is formed integral with the mandrel the V may be formed by a flap extending from the mandrel.

The proportion of the circumference of the mandrel sealed by the sealing means should be as high as possible, with the gap in the sealing means being sized to accommodate the pathway between the medicament reservoir and the inhalation chamber. Preferably the sealing ring should extend for about 250° - 330° around the mandrel and more preferably for about 300°.

Since the sealing ring is formed from resilient material it can be held in position during assembly of the device by this resilience. During use axial and rotational movement may be constrained by shoulder features on the mandrel collar. Additionally, or alternatively, the sealing ring may be held in position by an adhesive bond between the sealing ring and the mandrel.

Thus, according to a further aspect of the invention there is provided a sealing means comprising a partial ring extending about  $250^{\circ}$  -  $330^{\circ}$ , preferably about  $300^{\circ}$ , of a full ring circumference, whose cross section is generally V shaped.

- 5 The present invention is related to devices described in EP 407028 and EP 691865 which are hereby incorporated by reference. An embodiment of the present invention will now be described by way of example, with reference to the following drawings, in which:

Figure 1 is a longitudinal view in partial section of a device according to the present  
10 invention;

Figure 2 is a longitudinal view in partial section of the device of Figure 1 in the second metering position;

- 15 Figure 3 is a longitudinal section showing in detail the position of the sealing ring and through-going pathway of a device according to the invention in the first/rest position;

Figure 4 is a longitudinal section of a portion of the device of Figure 3 showing the position of the sealing ring and shoulder features;

20

Figure 5 is a perspective view of a sealing ring according to a preferred embodiment of the invention.

A device according to the invention includes a housing (1) having a mandrel (54) and a through-going pathway (2) connecting an air inlet (3) with an air outlet in the form of mouthpiece (4). A dispersion chamber (5) having tangential air inlets (6,6a) is located in the through-going pathway between air inlet (3) and mouthpiece (4).

- 5 A generally cylindrical medicament reservoir (7) containing an annular compacted body of powdered inhalation medicament (8) is rotatably mounted on the mandrel (54) adjacent to the through-going pathway (2) up stream from the dispersion chamber (5). Sealing ring (50) is mounted between medicament reservoir (7) and a housing collar (55) located on mandrel (54), being constrained from rotation and axial movement by shoulder features  
10 (52,53) on the mandrel collar (55).

- A shutter (9) comprising a metal blade (10) is mounted on a carrier (11) which is adapted to move axially within the housing between a first/rest position in which the compacted body (8) is isolated from the through-going pathway (2), and a second/metering position in which  
15 the compacted body (8) is in communication with the through-going pathway (2). The end of carrier (11) remote from the shutter (9) is provided with a lug (12) adapted to interact with a cam (13) provided on the inside of a drive sleeve (14) rotatably mounted on the housing (1). The carrier (11) is biased against the cam (13) by a half cantilever (15) provided on the carrier (11) which bears against an exterior wall of the dispersion chamber  
20 (5). The end of the carrier (11) remote from the shutter (9) is also provided with a disc (16) having a diameter generally corresponding to that of the interior of the housing (1). Disc (16) thus separates the cam (13) and reservoir drive mechanism (described below)



from the through-going pathway (2) thus reducing the risk of ingress of medicament into the drive mechanism.

Drive sleeve (14) is also provided with a reservoir drive mechanism (not shown) which is adapted to rotate the medicament reservoir (7) through a predetermined angle relative to the housing (1), the angle of rotation being limited by a stop (17) provided on the exterior of the housing.

A helical blade (18) is fixedly mounted on the mandrel of the housing between the reservoir (7) and the mouthpiece (4), such that the blade (18) abuts against the face of the body of compacted medicament (8) contained in the reservoir (7). Blade (18) comprises the upper surface of collar (55) as best shown in Figure 4. The body of compacted medicament (8) is further urged towards blade (18) by a compression spring (19) which acts against the outer wall of medicament reservoir (5) and the interior of drive sleeve (14).

15

In use, drive sleeve (14) is rotated in the direction of arrow A in Figure 1. The initial part of the rotation causes the cam (13) to move carrier (11) axially within the housing (1) towards the mouthpiece (4). The shutter (9) thus moves from the first/rest position [Figure 1] to the second/metering position [Figure 2]. Once the compacted body (7) is in communication with the through-going pathway (2), further rotation operates the reservoir drive means (not shown) thus advancing the reservoir (7) and compacted body (8) through an angle of 60°, the degree of rotation being limited by stop (17) provided on the outside of

20

the housing (1). As the reservoir (7) rotates helical blade (18) abrades a predetermined quantity of powdered medicament from the face of compacted body (8).

The drive sleeve (14) is then rotated in the direct of arrow B in Figure 2, Cam surface (13) rotates back to its original position allowing the shutter (9) to return to its first/rest position under the bias of cantilever (15). Friction between the sealing ring (50) and medicament reservoir (7) prevents any tendency for the medicament reservoir to move in direction B as drive sleeve (14) is returned to the starting position. As the shutter (9) returns to the first/rest position the metal blade (10) severs the abraded dose of medicament from the compacted body (8), the dose being deposited in the through-going pathway (2). The patient then inhales at the mouthpiece (4) drawing air through air inlet (3) and through-going pathway (2).

The dose of medicament is drawn into dispersion chamber (5) where it is entrained in the air flow and inhaled by the patient. During inhalation the shutter (9) prevents additional medicament from being scoured from the compacted body (8) since it isolates the compacted body (8) from the through-going pathway (2).

## Example

Devices as described above were filled with a powder compact comprising medicament and lactose. One set was filled with a composition consisting of Nedocromil Sodium, lactose

and flavouring. A second set was filled with a composition consisting of Salbutamol and lactose. The devices were tested as follows. The device was actuated as described above to place a metered dose of medicament in the through going pathway (2). This dose was removed from the pathway and its weight measured. The device was then placed in a mechanical shaker and shaken vigorously for some minutes. The device was then visually inspected for powder leakage. If this was found to be excessive the device was failed. The test was repeated until the device failed or until the powder compact was exhausted.

Devices containing Nedocromil Sodium compacts failed after 1 - 5 actuations with no seal present. The tests were repeated with two seals according to the present invention.

In the first test a seal composed of ABS rubber was used. This had a generally U shape with the base of the U much thicker than the arms and the base of the U facing the powder compact. The seal extended 305° around the circumference of the mandrel

15

In the second test a seal composed of polypropylene was used. The grade used was Novelen 248TC supplied by Targor. This seal had a generally V shaped cross section with the point of the V facing towards the powder compact. The seal extended 295° around the circumference of the mandrel.

20

All devices tested delivered in excess of 100 doses of medicament, which exhausted the medicament compact.

Devices containing Salbutamol compacts also failed after 1 - 5 actuations with no seal. With a seal composed of polypropylene as described above for Nedocromil Sodium the devices delivered between 73 and 158 doses before failing. The maximum number of doses possible was around 200.


### Claims

1. A medicament inhalation device including a housing having a through-going pathway connecting an air inlet with an air outlet, a medicament reservoir adapted to receive a compacted body of powdered medicament, an inner mandrel around which the medicament reservoir rotates and metering means for dispensing a predetermined dose of medicament from the reservoir into the pathway, the metering means including means for abrading the compacted body; characterised in that there is provided between the medicament reservoir and the inner mandrel of the device a sealing means extending round less than  $360^{\circ}$  of the mandrel.
2. A medicament inhalation device including a housing having a through-going pathway connecting an air inlet with an air outlet, a medicament reservoir containing a compacted body of powdered medicament, an inner mandrel around which the medicament reservoir rotates and metering means for dispensing a predetermined dose of medicament from the reservoir into the pathway, the metering means including means for abrading the compacted body; characterised in that there is provided between the medicament reservoir and the inner mandrel of the device a sealing means extending round less than  $360^{\circ}$  of the mandrel.
3. A medicament inhalation device according to claims 1 - 2 in which the sealing means comprise a feature forming an integral part of the inner mandrel of the device.

4. A medicament inhalation device according to claims 1 - 2 in which the sealing means comprise a feature formed on the inner mandrel of the device during production of the inner mandrel.
- 5 5. A medicament inhalation device according to claims 1 - 2 in which the sealing means comprise a separate partial sealing ring.
6. A medicament inhalation device according to claims 1 to 5 in which the sealing means is adapted to provide a frictional braking force on the medicament reservoir  
10 sufficient to prevent movement of the medicament reservoir when the ratchet mechanism designed to cause rotation of the reservoir is returning to its starting position but which force is not so large as to make the device difficult to operate by a child or infirm adult.
7. A medicament inhalation device according to claim 6 in which the frictional braking  
15 force is in the range of 0.1 - 0.6 Nm torque.
8. A medicament inhalation device according to claims 1 to 7 in which the sealing means has a generally V shaped cross section.
- 20 9. A medicament inhalation device according to claims 1 to 8 in which the sealing means extends for about 250° to 330° around the mandrel.

10. A medicament inhalation device according to claims 1 to 8 in which the sealing means extends about  $300^{\circ}$  around the mandrel.
11. A medicament inhalation device according to claims 1 to 10 in which the sealing means is constructed from a polyolefin material.
12. A medicament inhalation device according to claims 1 - 11 in which the sealing means is constructed from polypropylene.
- 10 13. A sealing means comprising a partial ring extending about  $250^{\circ}$  -  $330^{\circ}$  of a full ring circumference whose cross section is generally V shaped.
14. A sealing means comprising a partial ring extending  $300^{\circ}$  of a full ring circumference whose cross section is generally V shaped.


1/5



**Fig. 1**




2/5




*Fig. 2*

3/5




*Fig. 3*

4/5



*Fig. 4*

5/5



***Fig. 5***

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/03170

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M F16J B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 691 865 B (FISONS PLC) 14 May 1997 cited in the application see claim 1; figures ---	1
A	US 5 673 685 A (HEIDE HELMUT ET AL) 7 October 1997 see abstract; figure 1 ---	1
X	US 5 475 467 A (WATANABE KAZUSHI ET AL) 12 December 1995	13,14
A	see column 14, line 29 - line 56; figure 27 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 February 1999

Date of mailing of the international search report

03/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

# INTERNATIONAL SEARCH REPORT

Int. application No.

PCT/GB 98/ 03170

## Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
  
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
  
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
  
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

**FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210**

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-12

Inhaler

2. Claims: 13, 14

Sealing means

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/03170

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0691865 B	17-01-1996	AU 677311 B	17-04-1997
		AU 6433694 A	24-10-1994
		DE 69403204 D	19-06-1997
		DE 69403204 T	25-09-1997
		EP 0691865 A	17-01-1996
		FI 954597 A	28-09-1995
		GR 3024123 T	31-10-1997
		JP 8509626 T	15-10-1996
		NO 953757 A	22-09-1995
		US 5678538 A	21-10-1997
		AT 152920 T	15-05-1997
		CA 2159622 A	13-10-1994
		DK 691865 T	20-10-1997
		ES 2101524 T	01-07-1997
		WO 9422515 A	13-10-1994
		IL 109185 A	30-09-1997
		NZ 263595 A	29-01-1997
		SG 43138 A	17-10-1997
US 5673685 A	07-10-1997	AT 158951 T	15-10-1997
		AU 686560 B	12-02-1998
		AU 4066593 A	30-12-1993
		CA 2136835 A	09-12-1993
		DE 9307115 U	02-09-1993
		DE 59307510 D	13-11-1997
		WO 9324165 A	09-12-1993
		EP 0642366 A	15-03-1995
		ES 2118234 T	16-09-1998
		FI 945589 A	28-11-1994
		NO 944528 A	25-11-1994
US 5475467 A	12-12-1995	JP 6308819 A	04-11-1994
		JP 7013390 A	17-01-1995
		US 5697021 A	09-12-1997